





CONSTANCE




1Q11




1Q12




1Q13




2F98




3S23



3S24




4H85



4H86




53A5



53A6



6D00



7H48



8L48

Konstruktion Construction Description	1/10" Getuftete Schlinge, strukturiert 1/10" Tufted loop pile, structured 1/10" Bouclé tufté, structuré
Polnutschicht Pile material Composition de la fibre	100 % PA 6, ECONYL®
Strapazierwert Durability rating Usage	EN 1307 stark 23 heavy 23 fort 23
Komfortwert Comfort class Confort	Komfortklasse LC2 Luxury class LC2 Classe confort LC2
Stuhlrolleneignung Castor chair use Effet d'une chaise à roulette	gelegentliche Nutzung occasional use utilisation occasionnelle
Gesamtdicke Total thickness Epaisseur totale	EN 1307 ≈ 6,5 mm
Gesamtgewicht Total weight Poids total	EN 1307 ≈ 1.700 g/m ²
Poleinsatzgewicht Pile weight Poids de velours	EN 1307 ≈ 720 g/m ²
Brandverhalten Fire rating Comportement au feu	DIN EN 13501-1 C _{fl} -s1
Trittschallschutz Impact noise insulation Isolation acoustique	DIN EN ISO 10140 ≥ 20 dB

ECONYL
REGENERATED NYLON

Broadloom



