



Konstruktion   Construction   Description	1/10" Getufteter Shag, Frisé, meliert   1/10" Tufted shag, frise, mottled   1/10" Shag tufté, frisé, mélangé
Polnutschicht   Pile material   Composition de la fibre	100% PA 6.6
Strapazierwert   Durability rating   Usage	EN 1307 extrem 33   33 extreme   33 extrême
Komfortwert   Comfort class   Confort	Komfortklasse LC5   Luxury class LC5   Classe confort LC5
Stuhlrolleneignung   Castor chair use   Effet d'une chaise à roulette	intensive Nutzung   intensive use   utilisation intensive
Gesamtdicke   Total thickness   Epaisseur totale	EN 1307 Broadloom: ≈ 10,7 mm   Carpet tile: ≈ 12,5 mm
Gesamtgewicht   Total weight   Poids total	EN 1307 Broadloom: ≈ 2.050 g/m <sup>2</sup>   Carpet tile: ≈ 4.450 g/m <sup>2</sup>
Poleinsatzgewicht   Pile weight   Poids de velours	EN 1307 ≈ 1.260 g/m <sup>2</sup>
Brandverhalten   Fire rating   Comportement au feu	DIN EN 13501-1 Broadloom: C <sub>fl</sub> -s1   Carpet tile 50 × 50 cm: B <sub>fl</sub> -s1* ASTM E 648 + ASTM D2859
Trittschallschutz   Impact noise insulation   Isolation acoustique	DIN EN ISO 10140 33 dB
Schallabsorptionsgrad   Sound absorption   Absorption phonique	DIN EN ISO 354 Broadloom: α <sub>w</sub> 0,25   Carpet tile: α <sub>w</sub> 0,30



\* Bei anderen Maßen abweichend | Different for other sizes | Différent pour les autres dimensions



