



1Q00




1Q01




3N90



3S17



3S18



4F93



5V76



5V77



54A2



54A3



6C62




7H39



8L34



9F13



9H16

Konstruktion Construction Description		1/10" Getuftete Schlinge, strukturiert 1/10" Tufted loop pile, structured 1/10" Bouclé tufté, structuré
Polnutschicht Pile material Composition de la fibre		100 % PA 6.6
Strapazierwert Durability rating Usage	EN 1307	stark 23 heavy 23 fort 23
Komfortwert Comfort class Confort		Komfortklasse LC1 Luxury class LC1 Classe confort LC1
Stuhlrolleneignung Castor chair use Effet d'une chaise à roulette		gelegentliche Nutzung occasional use utilisation occasionnelle
Gesamtstärke Total thickness Epaisseur totale	EN 1307	≈ 8,3 mm
Gesamtgewicht Total weight Poids total	EN 1307	≈ 1.830 g/m ²
Poleinsatzgewicht Pile weight Poids de velours	EN 1307	≈ 640 g/m ²
Brandverhalten Fire rating Comportement au feu	DIN EN 13501-1	B _f -s1
Trittschallschutz Impact noise insulation Isolation acoustique	DIN EN ISO 10140	28 dB
Schallabsorptionsgrad Sound absorption Absorption phonique	DIN EN ISO 354	α _w 0,20

Broadloom



