



1M78




1M79



3P83



3P84




4G33



5W72



5W73



5W74



5W87



8J50



9F60



9F61



9F62

Konstruktion   Construction   Description		1/10" Getuftete Schlinge, tuftgemustert   1/10" Tufted loop pile, tuft patterned   1/10" Bouclé tufté, tufté à dessin
Polnutschicht   Pile material   Composition de la fibre		100 % PA 6.6
Strapazierwert   Durability rating   Usage	EN 1307	extrem 33   33 extreme   33 extrême
Komfortwert   Comfort class   Confort		Komfortklasse LC2   Luxury class LC2   Classe confort LC2
Stuhlrolleneignung   Castor chair use   Effet d'une chaise à roulette		intensive Nutzung   intensive use   utilisation intensive
Gesamtstärke   Total thickness   Epaisseur totale	EN 1307	Broadloom: ca. 5,1 mm   Carpet tile: ca. 8,8 mm
Gesamtgewicht   Total weight   Poids total	EN 1307	Broadloom: ca. 1.690 g/m <sup>2</sup>   Carpet tile: ca. 3.750 g/m <sup>2</sup>
Poleinsatzgewicht   Pile weight   Poids de velours	EN 1307	≈ 750 g/m <sup>2</sup>
Brandverhalten   Fire rating   Comportement au feu	DIN EN 13501-1	Broadloom: C <sub>fl</sub> -s1   Carpet tile 50 x 50: Bfl-s1
Trittschallschutz   Impact noise insulation   Isolation acoustique	DIN EN ISO 10140	Broadloom: 22 dB   Carpet tile: >20 dB
Schallabsorptionsgrad   Sound absorption   Absorption phonique	DIN EN ISO 354	Broadloom: aw 0,10

**Broadloom**

**Carpet tile**



# DAS/TEPPICH/WERK

1 8 8 3

